



Dimensions

in/mm

SMART-DRY 6 ALL-PURPOSE DRYING CABINET NFPA 1851 COMPLIANT

STANDARD FEATURES

- Gentle drying without mechanical action.
- · Dries from the inside and outside simultaneously using a dual circulation system.
- Programmable control.
- 6 detachable hangers are included in the standard design.
- Drying capacity of 6 large protective suits.
- Program ends with "cool down" to room temperature.
- Double overheat protection with backup sensor for increased safety.
- Interior lighting.
- 71 inches wide which allows for more room between the gear for faster drying.
- Easy to navigate programs with display, buttons, and braille.
- · Adjustable preset start time.
- Adjustable feet from the inside of the cabinet.
- Powder coated galvanized steel.


OPTIONAL FEATURES

- Detachable racks for gloves.
- Detachable racks for boots.
- · Door hook racks attached on the inside of the door for additional accessories.

HUMIDITY TRACKING SYSTEM - HTS

• The Smart-Dry 6 All-Purpose Drying Cabinet is equipped with the Humidity Tracking System (HTS) with temperature and humidity sensors. Senses the moisture level and interrupts the drying process when the laundry is dry.

D



111/111111					
Smart-Dry 6 All-Purpose Drying Cabinet	Width	Depth	Height	Depth with door	Exhaust position from back
	71 / 1800	31.5 / 800	77 / 1955	62.6 / 1590	9.84 / 250

С

Ε

TECHNICAL SPECIFICATIONS SMART-DRY 6 ALL-PURPOSE DRYING CABINET

Machine Type		Drying Cabinet
Product Name		Smart-Dry 6
Product No.		SDC-6
Main Data		
Туре		Air vented
Capacity, sets of turnout gear		6
Capacity (dry weight)	lbs / kg	55 / 25
Interior capacity	cu ft / L	73.1 / 2070
Drying capacity	oz/min / g/min	2 / 55
Energy consumption	kWh	6.7
Languages		8
Noise emission	dB(A)	65
Electrical Installation		
Electrical connection	3 phase	208-240v, 3ph, 60Hz, 12.45kw, 40amp
Electrical connection, (upon request)	1 phase	208-240v, 1ph, 60Hz, 9.45kw, 60amp
Dimensions		
Outer: width × depth × height	in / mm	71 × 31.5 × 77 / 1800 × 800 × 1955
Shipping: length × width × height	in / mm	75 × 30 × 50 / 1905 × 762 × 1270
Weight		
Weight	lbs / kg	441 / 200
Shipping weight	lbs / kg	600 / 272
Ventilation		
Outlet exhaust	Ø in / mm	6 / 152
Outlet air flow	cfm / m³/h	210 / 350
Pressure drop, max	psf / Pa	4.4 / 210
Maximum air flow (at 0% pressure)	cfm / m³/h	383 / 650
	,	,
Optional Accessories		
Hooks for drying cabinet door: 3 separate rows with 4 hooks on each, 1 set = 1 door	Product No.	SDDH
Hanger for boots		
	Product No.	SDBH

For freight cost savings, the drying cabinet ships knocked down in a crate. Assembly is required.

