



TEAM WENDY® SAR TACTICAL™

The Team Wendy® SAR TACTICAL™ is the first purpose-built search and rescue helmet to provide tactical accessory mounting capabilities while meeting key industrial and mountaineering performance standards.

PERFORMANCE STANDARDS

- BS EN 12492:2012 (Mountaineering)
- BS EN 1385:2012 (Whitewater)
- ACH Blunt Impact (AR/PD10-02, 16Dec'13)
- Off-Crown Shock Absorption (BS EN 14052:2012)

Environmental Conditions / MIL-STD-810G Methods

- > 501.5P1 High Temperature
- > 502.5P1 Low Temperature
- > 507.5 Humidity
- > 509.5 Salt Fog
- > 510.5PII Blowing Sand/Dust
- 514.6 Loose Cargo Vibration
- 500.5PI Low Pressure (Altitude)

WEIGHT

> 0.72 kg (1.59 lbs)



SIZING

SINGLE SIZE

Head Circumference (cm)
Head Circumference (in)
Hat Size (USA)

53-63 20 7/8-24 3/4 6 5/8-7 7/8

SHELL ASSEMBLY

- > High-cut shell with unique geometry for optimal fit
- Integrated machined aluminum (6061) shroud insert with type III hard anodizing compatible with all standard issue NVG mounts
- > Built-in accessory rails and goggle posts

MATERIALS

- > Shell: polycarbonate copolymer
- Side Rails and Vent Covers: Glass-reinforced polycarbonate
- Hardware: Stainless steel with MIL-DTL-13924D black oxide coating

LINER SYSTEM

- High performance-impact liner with two sets of comfort pads (thin and thick) for optimized fit
- Meets shock absorption requirements of BS EN 12492:2012 and BS EN 1385:2012
- Meets multi-hit ACH Blunt Impact requirement per AR/PD10-02, 16Dec'13 (Note: Liner material is frangible. Replace helmet after any significant impact.)

MATERIALS

- Impact Liner: Expanded polystyrene (EPS)
- Comfort Pads: Proprietary Zorbium® viscoelastic foam with water-resistant film and antimicrobial wicking fabric covering

RETENTION SYSTEM

- Integrated BOA® Fit System for optimized stability and fit with one-handed quick release
- MIL-DTL-32067 leather chin cup
- Cam Lock sliders for one-handed adjustment and secure fit

MATERIALS

- BOA® Fit System with micro-adjustable dial, coated stainless steel cable and low friction guides
- > 5/8" nylon webbing
- Acetal buckles and cams
- Antimicrobial wicking headband sleeves

COLORS

Black(FED-STD-595C #37031)

Blue (Pantone 286C)

High VizG reen (Pantone 2290C)

Red(FED-STD-595C #11105) USCG Orange(FED-STD-595C #12197)

White(FED-STD-595C #17865)

Yellow(FED-STD-595C# 13655)

Rails,S hrouda nd Vent Covers MedG unshipG ray(FED-STD-595C #36081)

AVAILABLE ACCESSORIES

EXFIL® PELTOR™ OUICK RELEASE ADAPTERS

Provides direct rail mount of all Peltor™ ComTac™ systems

EXFIL® PICATINNY QUICK RELEASE RAIL ADAPTERS

Tool-free accessory attachment, includes two 5-slot Picatinny rails

SAR SOLAS REFLECTIVE KIT

3M[™] Scotchlite™ Reflective Material is SOLAS / USCG approved

SHROUD HEADLAMP ADAPTER

Allows standard headlamps with elastic straps that pass behind the headlamp to attach to a helmet with a shroud

Full list of compatible accessories available on TeamWendy.com

SCAN/CLICK FOR PART NUMBERS



TW52485_SAR TACTICAL Data Sheet | Copyright © 2024 Team Wendy*. All rights reserved.

