



“LEADER OF THE PACK”

7202 SE International Court
P.O. Box 3404
Bartlesville, OK 74006
1-800-260-9950
1-918-333-2000
1-918-333-2004 Fax
sales@huskyportable.com
www.huskyportable.com

INSTRUCTIONS, WARNINGS & WARRANTIES FOR [HUSKY PORTABLE](http://www.huskyportable.com)
[CONTAINMENT FOLDING FRAME TANKS](http://www.huskyportable.com)

INSTRUCTIONS:

1. Upon delivery of your tank remove Folding Frame Tank from box and cut plastic ties holding the tank closed. Your tank is ready to be placed in its rack or its compartment.
2. To deploy remove from rack or compartment, unfold tank.
3. Pull any wrinkles out of the floor and be sure the drain tube(s) is connected to the top of the frame.
4. Fill with water.
5. To drain unhook drain tube(s).
6. Liner material is mildew and rot resistant, however to clean and let dry before storing will help longevity.

WARNINGS:

1. A ground cover placed under the tank is recommended to reduce the risk of damage to the floor of the tank.

WARRANTIES:

1. Life Time warranty on all welded seams of the frame tank.

Proper Folding

To fold your Husky Frame Tank it is best with two (2) people. Start at the folding points of the frame at opposites sides. Each person reaches down with their right hand and grabs the easy lift handle pulling up the liner at the same time pushing in the frame. There will be another easy lift handle for the left hand to grab to pull up the liner at the same time pushing in the frame. Using your legs push the frame tank together as far as you can go. At this point the easy lift handles should be pulled up above the top rail of the frame. Both individuals can grasp the long sides of the frame and pull inward. The liner will need to be somewhat accordion folded to allow for the best compact folded size. When completed folded the liner should not protrude out the bottom or top of the frame; the liner should be completely contained within the frame.

Proper Unfolding

To unfold your Husky Frame Tank it is best with two (2) people. Each individual should grab one side of the long side of the frame and pull away from the other. Once fully opened take the wrinkles out of the floor of the tank by using your hands to pull the floor close to each frame side.